

JACK Audio Connection Kit [(default)] Stopped.

Start Stop Stopped -- -- -- Quit
Messages Status
Connect Patchbay Playback Controls About...

Setup - JACK Audio Connection Kit

- Settings
- Options
- Display
- Misc

Preset Name: (default) Save Delete

Server

Server Path: /usr/bin/jackd Driver: alsa

Parameters

| | | |
|--|-----------------------|----------------------------|
| <input checked="" type="checkbox"/> Realtime | Priority: 40 | Interface: (default) |
| <input checked="" type="checkbox"/> No Memory Lock | Frames/Period: 512 | Dither: None |
| <input type="checkbox"/> Unlock Memory | Sample Rate: 48000 | Audio: Duplex |
| <input type="checkbox"/> Soft Mode | Periods/Buffer: 5 | Input Device: hw:1 |
| <input type="checkbox"/> Monitor | Word Length: 16 | Output Device: hw:1 |
| <input type="checkbox"/> Force 16bit | Wait (usec): 21333 | Input Channels: (default) |
| <input type="checkbox"/> H/W Monitor | Channels: (default) | Output Channels: (default) |
| <input type="checkbox"/> H/W Meter | Port Maximum: 256 | Input Latency: (default) |
| <input type="checkbox"/> Ignore H/W | Timeout (msec): 500 | Output Latency: (default) |
| <input type="checkbox"/> Verbose messages | MIDI Driver: none | Latency: 53.3 msec |
| | Start Delay (secs): 2 | |

OK Cancel